

Readabilitu IIO m

452 GB 9020



(non contractual picture)









Composition

1 scoreboard made of 3 modules

3 control consoles

3 carrying cases for control consoles

3 mains cable

Junction box and transmission cables (for cable controlled version)

Operating and installation instructions

Description

Indoor – tropicalized electronic parts for ice rink atmosphere Use:

Radio (868 MHz) or cable Transmission: Readability: 110m, angle >160° **Dimensions:** 3700 x 1150 x 90mm

Weight: 68 kg

Power supply: 230V / 50-60Hz

Protection: Unbreakable mat polycarbonate front face (DIN 18032-3)

Integrated Horn: 116dB at 1m

Mains cable: 25 m - Type: 230V, 3G, 0.75 mm²

Cable controlled: For cable controlled models or radio controlled models with cable set:

> Junction Box + 50 m transmission cable (scoreboard/junction box) -Type: phone cable 2 pairs 6/10th + 10 m transmission cable DIN/DIN

(junction box/console)

Display functions

Main module:

2 x 2 red LED digits (25 cm) Score: 1 green LED digit (20 cm) Period:

2 x 1 green LED dot Time stop indicator:

Timer/Rest period: 4 white LED digits (25 cm) + blinking points

Time out indicator: 2 x 1 yellow LED dot

Day time: when the scoreboard is not in use

Lateral modules:

Exclusions timers: 2 x 3 yellow LED digits (15cm) (for each module)

Display of 2 penalties per team

Penalty indicators: 6 red LED dots for 2', 5' and misconduct (10') penalties

(for each module)

Control consoles

3 consoles: (340 x 175 x 60 mm) with LCD screen with 2 lanes of 20 characters (9mm high)

1 Main console: management of the main functions

2 Control consoles for exclusion timers

Hold the consoles in charge when there are not in use. (Autonomy max 16 h) 1 charger:

Connexion plugs: DIN between the consoles

USB Port: For program update or connect PC keyboard

Programme: Ice Hockey + « Free mode » to create your own sport discipline or for

additional sports

Saved sport programs: create and save your own sport programs with

personalized settings

Multilingual Programme

Options

TV Interface (RS 485): Data transmission for TV broadcasting

Sound Interface: Connection with sport hall sound system - Horn sound amplifier

DCF or GPS Antenna: For accurate time synchronisation

Cable set: Cable mode for radio controlled scoreboard

Goal indicators: Goal and time stop indicators (pair) - cable controlled.





452 GB 9020_GB_A