

Cricket



FCB





(non binding picture)



Composition

1 scoreboard (made of 1 module)

1 control console

1 carrying case for control console

1 mains cable

Operating and installation instructions

Technical description

Use: Outdoor

Transmission :Radio (868 MHz) or cableReadability :60m, angle >160°Dimensions :2100 x 1200 x 90 mm

Weight: 42 kg

Power supply: 230V / 50-60Hz

Protection : unbreakable mat polycarbonate front face (DIN 18032-3) **Mains cable (supplied) :** 5m (socket not supplied) – Typ: 230V, 3G, 0.75 mm²

Cable controlled: for cable controlled models or radio controlled models with cable set

Junction box + 50m transmission cable (scoreboard / junction box) — Type: phone cable 2 pairs 6/10th + 10m transmission cable DIN/DIN

(junction box / console)

Installation: on I-Beams(Adjustable fixing) or wall-mounted (with clamps supplied)

Brightness: adjustable from the control console

Display functions

SCORE:2 x 2 red LED digits (16cm)TOTAL:3 red LED digits (16cm)BATSMAN:2 x 3 red LED digits (16cm)LASTMAN:3 red LED digits (16cm)WKTS:1 red LED digit (16cm)OVERS:2 red LED digits (16cm)

Control consoles

1 console: (340 x 175 x 60 mm) with LCD-screen with 2 lanes of 20 characters (9mm high)

1 charger (radio): Hold the console in charge when not in use (Autonomy max. 16h)

USB Port : For program update or connect PC Keyboard

Programme: Cricket
Multilingual programme

Options

TV Interface (RS 485): Data transmission for TV broadcasting

Sound Interface: Connection with sport hall sound system - Horn sound amplifier

Cable set:Cable mode for radio controlled scoreboardAdvertising panels:Black panels (advertising stickers on demand)

FCB_GB_A