

## ELECTRONIC TIMERS Indoor Readability 35m

## HC9.4



Available in 2 LED colors, red or yellow







(non contractual picture)

# Composition

1 Digital Clock

1 Infrared remote control

1 Cable control console for the timer

Operating and installation instructions

#### **Description**

Use: Indoor

Programming: Infra-red remote control

**Readability:** 35m, angle >160° **Dimensions:** 460 x 180 x 90mm

Weight: 3 kg

Power supply: 230V / 50-60Hz Power consumed: 15VA

**Protection:** Unbreakable mat polycarbonate front face

Mains cable (supplied): 5 m – Type: 230V, 3G, 0.75 mm<sup>2</sup>

#### Display functions

**Timer**: 4 red or yellow LED digits (9 cm) for:

- Count-up timer: hundredths / seconds / minutes (MM:SS)
- Count-down timer: (MM:SS)
- Timer mode: count-up or count-down from a set-value
- "Workout" modes: to manage sequences of exercises / rest periods.

#### Other available functions:



- Programming of the brightness (4 luminosity levels available)
- Eco-Mode: low luminosity between 23:00 and 06:00

#### Remote control

1 IR remote control (180 x 50 x 23 mm), clear range at 10m, for:

- Programming of the day time
- Programming of the date
- Programming of the display duration
- Programming of the transition effects
- Possibility to display a permanent information

1 cable control console: (140 x 150 x 40mm) cable 5m

- Programming of the timer
- Start / Stop / Reset the timer to 0

#### **Options**

**DCF or GPS Antenna:** For accurate time synchronisation **Sensor:** For automatic air temperature display

Slave clock Integrated buzzer

Tripod

HC9.4\_GB\_C