

MULTISPORT SHOT-CLOCKS Readability 130 m

BASKET BALL

4-SIDED SC24 TIMER SUPER PRO











(non contractual pictures)

Composition

2x 4-sided display units

1 control console

1 carrying case for control console

2 mains cable

2x junction boxes and transmission cables Operating and installation instructions

Description (per display unit)

Use: Indoor

Transmission: Cable. Works only with STRAMATEL Multisport scoreboard

Readability: 130m, angle >160° **Dimensions:** 640 x 770 x 770mm

Weight: 25 kg

Power supply: 230V / 50-60Hz

Power consumed: 143 VA

Protection: Unbreakable matt polycarbonate front face (DIN 18032-3)

Integrated Horns: 2 horns, 116dB at 1m

Mains cable (supplied): $1x25 \text{ m} - \text{Type: } 230\text{V}, 3\text{G}, 0.75 \text{ mm}^2$

Cable controlled: Junction Box + 25 m transmission cable (scoreboard/junction box) –

Type: DIN/DIN + 25 m transmission cable (junction box/main junction box) – Type:

phone cable 2 pairs 6/10th

Display functions (1 side of 1 display unit)

Shot-clock: 2 red LED digits (25 cm) + 1 point for display of seconds

and tenths of second

Game clock repeater: 4 yellow LED digits (16 cm) + blinking points

24/14s violation: 1 red LED point

Control consoles

1 console: (145 x 150 x 40 mm) with LCD screen with 1 lane of 20 characters (9mm high)

Shot-clock controller

Works only with STRAMATEL Multisport scoreboard

Options

Led Strips: Electric light to be installed behind the backboard (FIBA or Euro

league rules)

Support frame: Support frames for basketball backstops



SC24 TSP 4F 2017_GB _A